


- 1A-73.50
- 2A-108.50
- 3A-133.50
- 4A-153.25
- 5A-169.50
- 6A-183.50
- 7A-195.50
- 8A-205.75
- 9A-214.50
- 10A-222.25
- 11A-228.75
- 12A-234.25
- 13A-239.00
- 14A-242.50
- 15A-245.50
- 16A-247.50
- 17A-248.50
- 17B-248.50
- 16B-247.50
- 15B-245.50
- 14B-242.50
- 13B-239.00
- 12B-234.25
- 11B-228.75
- 10B-222.25
- 9B-214.50
- 8B-205.75
- 7B-195.50
- 6B-183.50
- 5B-169.50
- 4B-153.25
- 3B-133.50
- 2B-108.50
- 1B-73.50

CLIPS PLACED AT EVERY INTERSECTION FROM ROW TO SUPPORT CIRCUMFERENCE

ITEM	DESCRIPTION
1	CENTER CHALKLINE
2	NORMAL CHALKLINE SPACING 25"
2S	INNER ROW CHALKLINE SPACING 9"
	2 CLIPS (APPLIED AT THE TOP AND BOTTOM OF EVERY SYNTIRO INTERSECTION)

WARNING: DO NOT EXCEED 6" OF BOARD OVER HANG FROM SUPPORT

ITEM	AMOUNT
42" SYNTIRO'S	82
CLIPS	65

UNITS	TOTALS
LIN/FT	557.63'
FLASHING	43
OVR. WGHT	1,677 LBS